

ACCESSORIES FOR THE INSTALLATION OF ANTI-BURROWING BOARDS

- concrete panels replacing the bedding suitable for installing under classic mesh, welded wire mesh or welded panels
- digging boards are fixed to round and square posts using stabilization holders
- a length of 245 cm is suitable for PILOFOR panels, a length of 295 cm is suitable for other types of mesh and welded wire mesh



| description | length/height/width (mm) |
|--|--------------------------|
|  <p>smooth finish – without lock</p> | 2450/200/50 |
| | 2950/200/50 |
| | 2450/300/50 |
| | 2950/300/50 |
|  <p>one-sidedly scrubbed natural gravel-stone – without lock</p> | 2450/300/50 |
| | 2950/300/50 |
|  <p>one-sidedly scrubbed “Janiček board” (suitable for PILEG® system)</p> | 2000/300/50 |
| | NEW |

ACCESSORIES FOR THE INSTALLATION OF ANTI-BURROWING BOARDS

| description | |
|---|--|
|  <p>NEW PVC – straight height 200 mm Ø otvoru 38 mm</p> | |
|  <p>PVC – straight height 200 mm gap diameter 38 mm</p> | |
|  <p>PVC – straight height 300 mm square gap 60 × 60 mm for PILOFOR® posts</p> | |
|  <p>galvanized – straight* height 200 mm or 300 mm gap diameter 48 mm</p> | |
|  <p>galvanized – end* height 200 mm or 300 mm</p> | |
|  <p>PVC – end height 200 mm</p> | |
|  <p>PVC – end height 300 mm</p> | |
|  <p>NEW Galvanized + PVC stabilization holder for the Janiček board</p> | |
|  <p>NEW TEX screw 6.3 × 32 (self-screwing)</p> | |
|  <p>NEW TEX screw 6.3 × 50 (self-screwing)</p> | |